

Industrial dry vacuum cleaners - single phase

Vacuum cleaner with 3 motors. The filtering system is made of a polyester filter + cartridge filter. Manual filter shaking system. Removable dry container for maximum reliability. AS 40 KS is available in M and H filtration class.



PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
AS 40 KS	18961210993	1
AS 40 KS M	18961210994	1
AS 40 KS H	18961210995	1

TECHNICAL DATA

FEATURES

Voltage - Frequency	220-240 V~	50/60 Hz
Max power rating	W	3450
Rated power (nominal power)	W	2900
Container capacity	l	60
Useful capacity	l	40
Filtering surface (textile filter)	m ²	0,5
Filtering surface (cartridge filter)	m ²	1,06 (*) - 2,10 (**) - 4,20 (***)
Air flow rate	l/s	150
Vacuum	mbar	205
Noise level	db(A)	66,5
IP code	IPX4 (*) (**)	
Power supply cable	m	10
Weight (without accessories)	Kg	51
Dimensions	mm	765x560x1400

STANDARD ACCESSORIES Ø 50


TYPE	REF. NO.
Flexible hose 3 m (*)	6010712
Flexible hose 3 m (**) (***)	6010711
Curved extension tube Ø 50	2511700
Adjustable dry brush 0,40 m	6010052
Round brush	2511720
Crevice tool	2511730
Cartridge filter (filtering surface 1,06 m ²) (*)	2512743
Cartridge filter (filtering surface 2,10 m ²) (**)	2512076
Cartridge filter CLASS HEPA/H (filtering surface 4,20 m ²) (***)	2512078
Textile filter for manual filter shaking system	6895510
Connection Ø 50	2511710
Manual filter shaking system	---

OPTIONAL ACCESSORIES

TYPE	REF. NO.
Adjustable dry brush 0,50 m	6010062
Stainless steel dry and wet/dry thickener separator	1897006
Paper filter bag with cap 119 x 10 (**) (***)	6830030



CLOGGED FILTER
PRESSURE GAUGE



CONVEYOR IN THE TANK



VACUUM CLEANER
WITH 3 MOTORS



MANUAL FILTER
SHAKING SYSTEM



PRACTICAL BASKET
HOLDER FOR ACCESSORIES



DETACHABLE STAINLESS
STEEL CONTAINER



INTAKE Ø 90 (AS 40 KS)



INTAKE Ø 50 (AS 40 KS M/H)



(*) For AS 40 KS
 (**) For AS 40 KS M version
 (***) For AS 40 KS H version