

GPW 150.8 SP C

Cold water pressure washer - single-phase

The GPW 150.8 SP C is a professional cold water high pressure washer which, thanks to its 150 bar operating pressure and 8 l/min water flow rate, guarantees excellent cleaning results. The GPW 150.8 SP C is practical, manoeuvrable, and simple to use. It is equipped with a professional 3-ceramic piston pump with a connecting rod/crank system and brass pump head, which allows for pressure regulation as well as detergent suction. Extremely robust thanks to the resistant frame and stainless steel casing, this machine features the TDTS (Time Delayed Total Stop) safety system, which stops the motor 12 seconds after the trigger on the spray gun is released. The GPW 150.8 SP C is the ideal pressure washer for cleaning floors, walls, building facades, machinery, industrial equipment and for removing solid residues such as dust or debris.



PUMP WITH BRASS HEAD AND CERAMIC PISTONS



PRESSURE REGULATION AND BUILT-IN DETERGENT SUCTION



TIME DELAYED TOTAL STOP (TDTS) SAFETY SYSTEM



PRESSURE GAUGE ALWAYS VISIBLE DURING OPERATION



HOSE REEL (OPTIONAL)



LARGE WHEELS



FOLDING HANDLE



PROFESSIONAL STANDARD ACCESSORIES

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
GPW 150.8 SP C	94600062/1GPW	6

TECHNICAL DATA

FEATURES

Max pressure	bar-Mpa	150-15
Water flow rate	l/min	8
Voltage - Frequency	V ~ Hz	230V ~ 50 Hz
Power rating	kW	2,2
Pump	rpm	1450
Max water feed temperature	°C	50
IP code		IP54
Power supply cable	m	5
Weight (without accessories)	kg	42
Dimensions	mm	820x445x790

STANDARD ACCESSORIES

TYPE	REF. NO.
High pressure hose (10 m)	6180035/1
Spray gun AL15	6180040/1
Spray lance (50 cm)	6180043
Water nozzle	1000300/15025

OPTIONAL ACCESSORIES

TYPE	REF. NO.
Rotating nozzle 165 bar	1000381KIT28
Brass pipe cleaning nozzle	1000393/035K
Hose reel kit with 15 m hose	6000552/J
High pressure hose 250 bar (20 m)	6180037