

# GREEN PRO RACER R 85 FD 65 BC



## Ride-on scrubber dryers RACER SERIES

GREEN PRO RACER R 85 FD 65 BC is the ride-on scrubber dryer made of recycled plastic material, ideal for use in medium-sized areas. Compact and extremely maneuverable, GREEN PRO RACER can move effortlessly even in the tightest and most congested spaces, such as supermarket aisles and checkouts, avoiding obstacles quickly and effectively. The retractable brush head, which can adapt perfectly to any obstacle, makes Racer unparalleled in "close-to-wall" cleaning. The aluminum squeegee, with natural rubber blades supplied as standard, ensures the best drying results on all kinds of surfaces and, in the event of accidental bumps, is able to automatically move and retract under the machine structure ensuring maximum safety and ease of action. The ECO SYSTEM program reduces consumption and eliminates waste while maintaining the best cleaning performance and respecting the environment.



24% RECYCLED PLASTIC

### PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
GREEN PRO RACER R 85 FD 65 BC	13.0675.70	1

### GREEN GREEN DATA

#### FEATURES

Recycled plastic	%	24
Noise level	db(A)	57 (*)
Energy consumption per m <sup>2</sup>	Wh/m <sup>2</sup>	0.35
CO <sub>2</sub> emissions per m <sup>2</sup>	gCO <sub>2</sub> /m <sup>2</sup>	0.12

### PRO

#### TECHNICAL DATA

##### FEATURES

Cleaning width	mm	650
Squeegee width	mm	850
Productivity (theoretical - practical) m <sup>2</sup> /h		4000 - 2400
Power supply		Battery 24V
Installed power	W	2150
Advancement		with traction
IP code		IPX3

##### BATTERIES

Type	Gel battery set (2 pcs) 12V 105Ah	
Running time	h - min	2 h
Battery compartment dimensions x No	mm x No	380x540x310 X 1

##### BRUSHES

Pad diameter x No	mm - inch x No	330 - 13" x 2
Motor rating x No	W x No	500 x 2
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm <sup>2</sup>	32,5; 49,5 - 30;46

##### TRACTION

Motor rating	W	600
Driving speed	Km/h	6
Hill climbing ability (full load)	%	2
Hill climbing ability (empty)	%	12

### VACUUM

Motor rating	W	550
Vacuum	mbar - mmH <sub>2</sub> O	125 - 1250
Airflow rating	l/s	30

### TANK

Type		Double tank
Cleaning solution tank	l	80
Recovery tank	l	85
Weight (empty/with batteries)	Kg	206,20 - 278,20
Dimensions	mm	1375x880x1230

### STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
13" Polypropylene brush Ø 0,7 (**)	40.0011.00
Brush Solution Diffuser	96.0207.00
Splashguard	22.0712.00
Set natural rubber squeegee blades (front/rear)	96.0176.00
Gel battery set (2 pcs) 12V 105Ah	22.0724.00
On board battery charger 24V 13A	18.0095.00

### OPTIONAL ACCESSORIES

TYPE	REF. NO.
13" Polypropylene brush Ø 0,9	40.0111.00
13" Tynex brush Ø 0,9 grit 240	40.0215.00
Pad holder 330 mm (for 13" pad)	40.1004.00
Set polyurethane squeegee blades (front + rear)	96.0176.01
Chemical mixing system	96.0206.00
Headlight kit	96.0180.00
Blinking kit	96.0181.00
Corner drying kit	96.0182.00
Water Stop kit	96.0183.00
Fleet 4 You (***)	96.0212.00
Fleet & Key 4 You (****)	96.0213.00



ECO SYSTEM



"SILENT MODE" FUNCTION



CONTROL PANEL WITH  
DISPLAY AND WATER FLOW  
ADJUSTMENT



BRUSH SOLUTION DIFFUSER



"READY TO GO" FUNCTION



WIDE RECOVERY TANK  
OPENING: EASY TO CLEAN



FLEET 4 YOU (OPTIONAL)

(\*) Silent mode function

(\*\*) 2 brushes on standard equipment

(\*\*\*) On request and to be defined at time of order

Registered office: Riello Cleaning Machines S.p.A. Via Enrico Fermi, 43 - 37136 Verona (VR) - Italy.

Place of manufacturing: Dorno (PV) - Italy