

# GREEN PRO REXA 50 D 55 BC CHEM



## Walk behind scrubber dryers REXA 50 SERIES - with TRACTION

GREEN PRO REXA 50 D 55 BC CHEM is the new walk-behind scrubber-dryer designed by Ghibli also in an eco-friendly version. Its 50 litre capacity, 530 mm washing track, 750 mm suction width and 2650 m<sup>2</sup>/h productivity make it ideal for use in medium-sized areas, guaranteeing fast and effective results even in the most complex environments to clean. The machine's numerous functions such as Silent Mode, ECO System, and Brush Release, for automatic brush release, can be operated easily and intuitively via the practical control panel with integrated display. The ergonomic handle with Touch System gives the operator maximum flexibility and control while working. The LED front light allows the machine to be used even in poorly lit environments. A perfect mix of sustainability, efficiency and power, the Green Pro Rexa 50, although produced using regenerated plastic material, offers the same robustness and reliability that have always distinguished Ghibli machines.



22% RECYCLED PLASTIC



ECO SYSTEM



"SILENT MODE" FUNCTION



CHEMICAL MIXING SYSTEM



CONTROL PANEL WITH DISPLAY  
AND WATER FLOW REGULATION



BRUSH SOLUTION DIFFUSER



RECOVERY TANK: EASY  
ACCESS AND CLEANING



FLEET 4 YOU (OPTIONAL)

## PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
GREEN PRO REXA 50 D 55 BC CHEM	17.5055.70	1

## GREEN GREEN DATA

### FEATURES

Recycled plastic	%	22
Noise level	db(A)	< 70 (*)
Energy consumption per m <sup>2</sup>	Wh/m <sup>2</sup>	0.33
CO <sub>2</sub> emissions per m <sup>2</sup>	gCO <sub>2</sub> /m <sup>2</sup>	0.11

## PRO

### TECHNICAL DATA

#### FEATURES

Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m <sup>2</sup> /h	2650 - 1690
Power supply		Battery 24V
Installed power	W	1108
Advancement		with traction
IP code		IPX3

#### BATTERIES

Type	Gel battery set (2 pcs) 12V 105Ah	
Running time	h - min	2 h and 55 min
Battery compartment dimensions x No	mm x No	345x345x295x1

#### BRUSHES

Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm <sup>2</sup>	20.30 - 13.20

#### TRACTION

Motor rating	W	180
Driving speed	Km/h	5
Hill climbing ability (full load)	%	2
Hill climbing ability (empty)	%	12

## VACUUM

Motor rating	W	380
Vacuum	mbar - mmH <sub>2</sub> O	105 - 1050
Airflow rating	l/s	45

## TANK

Type	Double tank	
Cleaning solution tank	l	50
Recovery tank	l	50
Weight (empty/with batteries)	Kg	79.87 - 154.87
Dimensions	mm	1339x801x1069

## STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush Ø 0.7	40.0003.00
Brush Solution Diffuser	96.0207.00
Detachable brush deck splash guard (without bristles)	24.0266.00
Brush deck splash guard bristles	40.4012.00
Set front+rear natural rubber squeegee blades	96.0234.00
Gel battery set (2 pcs) 12V 105Ah	18.0001.00
On board charger 24V 11A	22.0875.00
Chemical mixing system	22.0872.00

## OPTIONAL ACCESSORIES

TYPE	REF. NO.
21" Polypropylene brush Ø 0.9	40.0103.00
21" Polypropylene brush Ø 1.2	40.0303.00
21" Tynex brush Ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.01
Set front + rear polyurethane squeegee blades	96.0234.01
Kit Water Stop	96.0233.00
Fleet 4 You (**)	96.0212.00
Fleet & Key 4 You (**)	96.0213.00

(\*) Silent mode function  
(\*\*) On request and to be defined at time of order

Registered office: Riello Cleaning Machines S.p.A. Via Enrico Fermi, 43 - 37136 Verona (VR) - Italy.  
Place of manufacturing: Dorno (PV) - Italy