

## Industrial dry vacuum cleaners - three-phase

Three-phase industrial vacuum cleaner, perfect for any industrial application requiring long and heavy-duty use for the suction of solids and dust. This model features an electronically balanced side channel blower with direct drive on the motor shaft. The absence of transmission devices makes the suction unit not only quiet and powerful, but also allows for continuous duty (24/7) without the need for routine maintenance, while the motor protection switch protects the turbine under all conditions. Power InDust 60 TP M is equipped with a vacuum gauge which, thanks to constant monitoring of the vacuum level, is able to detect the clogging level of the filters or other parts of the suction system. An M-class pocket filter with a large surface area (3 m<sup>2</sup>) retains the vacuumed dust while ensuring excellent air quality at the outlet. In addition, the practical manual filter shaker ensures extreme filter durability, preventing clogging, saturation and reduction of filtering capacity. The front suction inlet, located below the filter, allows for the simultaneous suction of dust and solids. The quick-release tank and sturdy trolley with non-marking wheels make it extremely easy to use.



### PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
POWER InDust 60 TP M	12268800001	1

### TECHNICAL DATA

#### FEATURES

FEATURES		
Voltage-Frequency	V~ Hz	380-420 V <sup>3</sup> ~ 50 Hz
Power	W	3450
Container capacity	l	60
Type of primary filter	Class M antistatic polyester	
Primary filter surface area	m <sup>2</sup>	3
Machine filtration class		M
Air load on primary filter	m <sup>3</sup> /m <sup>2</sup> h	106
Airflow max	l/s	88
Depression	mbar	280
Noise level	dB(A)	76
IP code for electrical components		IPX0
Power supply cable	m	10
Weight (without accessories)	Kg	101
Dimensions	mm	650x690x1860

### STANDARD ACCESSORIES Ø 80

TYPE	REF. NO.
Flexible hose 3 m	2511242
Polyester antistatic star filter (M class)	3001246

### OPTIONAL ACCESSORIES

TYPE	REF. NO.
Adjustable dry brush 0,40 m	6010052
Adjustable dry brush 0,50 m	6010062
Curved suction tube Ø 50	2511700
Round brush	2511720
Crevice tool	2511730
Connection Ø 50 (*)	2511710
Flexible hose 3 m (**)	6010711
Stainless steel dry and wet/dry thickener separator	1897006



QUIET AND POWERFUL



STURDY TROLLEY




MANUAL FILTER SHAKER



VACUUM GAUGE



M-CLASS STAR FILTER



GREAT CAPACITY



WIDE RANGE OF ANTISTATIC ACCESSORIES



EASY CLEANING AND MAINTENANCE



(\*) Mandatory for the use of round brush (2511720) or crevice tool (2511730)  
 (\*\*) Necessary for using dry and wet/dry thickener separator (1897006)