

## Walk behind scrubber dryers REXA 50 SERIES - with TRACTION

Rexa 50 SD 55 is the walk-behind scrubber-dryer designed to guarantee excellent performance in daily cleaning operations in medium-sized areas. Its 50 litre capacity, 530 mm washing track and 750 mm suction width ensure a productivity of approximately 2650 m<sup>2</sup>/h, guaranteeing fast and effective results even in the most complex areas to clean. The ergonomic handle with integrated dual-sensor Touch System allows precise control of the machine, making every work session easier and more comfortable. Rexa 50 SD (Simply Driven) is designed to guarantee the best washing and drying performance, combined with extreme ease of handling and use. A perfect mix that guarantees the best performance in use, making every cleaning operation easier and more functional. The high-efficiency vacuum motor provides high power while reducing consumption for more sustainable and cost-effective use. Daily maintenance is facilitated thanks to the recovery tank with a large opening, which facilitates inspection and cleaning, and the practical, easily removable debris tray, which allows for quick waste management. Rexa 50 SD is the ideal solution for those looking for a compact, efficient and user-friendly scrubber-dryer that combines high cleaning performance with practical and fast machine handling.



SIMPLIFIED CONTROL PANEL



ERGONOMIC HANDLE + INTEGRATED TOUCH SYSTEM



WIDE RECOVERY TANK: EASY ACCESS AND CLEANING



EASY ACCESS TO ALL MAIN COMPONENTS



PEDAL-OPERATED, ADJUSTABLE AND COMPACT SQUEEGEE



DEBRIS TRAY + INTAKE MOTOR FILTER



NEW BRUSH DECK: HIGH EFFICIENCY AND TOP PERFORMANCE



EXTRA DOWN PRESSURE (10 KG)

### PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
REXA 50 SD 55	10.5056.00	1
REXA 50 SD 55 BC	13.5056.00	1
REXA 50 SD 55 BC PLUS	15.5056.00	1

### TECHNICAL DATA

FEATURES		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m <sup>2</sup> /h	2650 - 1690
Power supply		Battery 24V
Installed power	W	1060
Advancement		With traction
IP code		IPX3

### BATTERIES

Type	Gel battery set (2 pcs) 12V 76Ah (*) - Gel battery set (2 pcs) 12V 105Ah (**)	
Running time	h - min	2 h and 12 min (*) - 2 h and 55 min (**)
Battery compartment dimensions x No	mm x No	345x345x295 X1

### BRUSHES

Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm <sup>2</sup>	20,30 - 13,20

### TRACTION

Motor rating	W	180
Driving speed	Km/h	5
Hill climbing ability (full load)	%	2
Hill climbing ability (empty)	%	12

### VACUUM

Motor rating	W	380
Vacuum	mbar - mmH <sub>2</sub> O	105 - 1050
Airflow rating	l/s	45
Noise level	dB(A)	<70

(\*) For BC version

(\*\*) For BC PLUS version