

REXA 50 SM 55



Walk behind scrubber dryers REXA 50 SERIES - MANUAL

Rexa 50 SM 55 is the walk-behind, manual scrubber-dryer designed for excellent performance in daily cleaning operations in medium-sized areas. 50 litre capacity, 530 mm cleaning width and 750 mm squeegee width ensure a productivity of approximately 2120 m²/h, guaranteeing fast and effective results even in the most complex environments to clean. The ergonomic handle with integrated dual-sensor Touch System allows precise control of the machine, making every work session easier and more comfortable. Rexa 50 SM (Simply Manual) is designed to combine the best washing and drying performance with extreme ease of use, perfectly combining practicality and economy, for professional results thanks to simple and immediate interaction with the operator. The high-efficiency suction motor guarantees high power while reducing consumption for more sustainable and convenient use. Daily maintenance is made easy thanks to the recovery tank with large opening, which facilitates inspection and cleaning, and the practical, easily removable debris tray, which allows for quick waste management. Rexa 50 SM is the ideal solution for those looking for a compact, efficient and user-friendly scrubber-dryer, capable of combining high cleaning performance with practical and fast machine management. Available in two configurations: a basic version and a full package, complete with batteries and charger, for a running time of more than 2.5 hours.



SIMPLIFIED CONTROL
PANEL



ERGONOMIC HANDLE
+ INTEGRATED TOUCH
SYSTEM



WIDE RECOVERY TANK:
EASY ACCESS AND
CLEANING



EASY ACCESS TO ALL MAIN
COMPONENTS



PEDAL-OPERATED,
ADJUSTABLE AND
COMPACT SQUEEGEE



DEBRIS TRAY + INTAKE
MOTOR FILTER



NEW BRUSH DECK: HIGH
EFFICIENCY AND TOP
PERFORMANCE



EXTRA DOWN PRESSURE
(10 KG)

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
REXA 50 SM 55	10.5058.00	1
REXA 50 SM 55 BC	13.5058.00	1

TECHNICAL DATA

FEATURES

Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m ² /h	2120 - 1270
Power supply		Battery 24V
Installed power	W	880
Advancement		Manual
IP code		IPX3

BATTERIES

Type	Gel battery set (2 pcs) 12V 76Ah (*)	
Running time	h - min	2 h and 36 min (*)
Battery compartment dimensions x No mm x No	345x345x295 X 1	

BRUSHES

Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm ²	20;30 - 13;20

TRACTION

Motor rating	W	--
Driving speed	Km/h	4
Hill climbing ability (full load)	%	2
Hill climbing ability (empty)	%	12

VACUUM

Motor rating	W	380
Vacuum	mbar - mmHg	105 - 1050
Airflow rating	l/s	45
Noise level	dB(A)	< 70

TANK

Type	Double tank	
Cleaning solution tank	l	50
Recovery tank	l	50
Weight (empty/with batteries)	Kg	78 - 137,5
Dimensions	mm	1339x801x1069

STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush Ø 0.7	40.0003.00
Brush Solution Diffuser	96.0207.00
Detachable brush deck splash guard (without bristles)	24.0266.00
Brush deck splash guard bristles	40.4012.00
Set front+rear natural rubber squeegee blades	96.0234.00
Gel battery set (2 pcs) 12V 76Ah (*)	18.0000.00
On board charger 24V 11A (*)	22.0875.00

OPTIONAL ACCESSORIES

TYPE	REF. NO.
21" Polypropylene brush Ø 0.9	40.0103.00
21" Polypropylene brush Ø 1.2	40.0303.00
21" Tynex brush Ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.01
Set front + rear polyurethane squeegee blades	96.0234.01
Kit Water Stop	96.0233.00

(*) For BC version