

Walk behind scrubber dryers REXA 50 SERIES - MANUAL

Rexa 50 SM 55 is the walk-behind, manual scrubber-dryer designed for excellent performance in daily cleaning operations in medium-sized areas. 50 litre capacity, 530 mm washing track and 750 mm suction width ensure a productivity of approximately 2120 m²/h, guaranteeing fast and effective results even in the most complex environments to clean. The ergonomic handle with integrated dual-sensor Touch System allows precise control of the machine, making every work session easier and more comfortable. Rexa 50 SM (Simply Manual) is designed to combine the best washing and drying performance with extreme ease of use, perfectly combining practicality and economy, for professional results thanks to simple and immediate interaction with the operator. The high-efficiency suction motor guarantees high power while reducing consumption for more sustainable and convenient use. Daily maintenance is made easy thanks to the recovery tank with large opening, which facilitates inspection and cleaning, and the practical, easily removable debris tray, which allows for quick waste management. Rexa 50 SM is the ideal solution for those looking for a compact, efficient and user-friendly scrubber-dryer, capable of combining high cleaning performance with practical and fast machine management.



SIMPLIFIED CONTROL
PANEL



ERGONOMIC HANDLE
+ INTEGRATED TOUCH
SYSTEM



WIDE RECOVERY TANK:
EASY ACCESS AND
CLEANING



EASY ACCESS TO ALL MAIN
COMPONENTS



PEDAL-OPERATED,
ADJUSTABLE AND
COMPACT SQUEEGEE



DEBRIS TRAY + INTAKE
MOTOR FILTER



NEW BRUSH DECK: HIGH
EFFICIENCY AND TOP
PERFORMANCE



EXTRA DOWN PRESSURE
(10 KG)

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
REXA 50 SM 55	10.5058.00	1
REXA 50 SM 55 BC	13.5058.00	1

TECHNICAL DATA

FEATURES

Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m ² /h	2120 - 1270
Power supply		Battery 24V
Installed power	W	880
Advancement		Manual
IP code		IPX3

BATTERIES

Type	Gel battery set (2 pcs) 12V 76Ah (*)	
Running time	h - min	2 h and 36 min (*)
Battery compartment dimensions x No	mm x No	345x345x295 X 1

BRUSHES

Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm ²	20,30 - 13,20

TRACTION

Motor rating	W	--
Driving speed	Km/h	4
Hill climbing ability (full load)	%	2
Hill climbing ability (empty)	%	12

VACUUM

Motor rating	W	380
Vacuum	mbar - mmH ₂ O	105 - 1050
Airflow rating	l/s	45
Noise level	dB(A)	<70

(*) For BC version