ROUND 45 D 55



Walk behind scrubber dryers **ROUND 45 - with TRACTION**

Round 45 D 55 TOUCH is the renowned Ghibli's scrubber dryer. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. The technical features and the high level innovations - 45 liters tank capacity, two hours and a half running time, the control panel with display, the "silent mode" function, the double brush pressure, the new chemical mixing System - make Round 45 something unique in its market segment, ideal for effective cleaning results in every kind of floor/environment. The wide cleaning path (21" single brush) and the adjustable speed (up to 5 km/h) allow a productivity of 2650 m²/h. ROUND 45 is now available with two important upgrades:

- thanks to the new sensor TOUCH SYSTEM, Ghibli patented, ROUND 45 can be moved and controlled only using a thumb: intuitive, user friendly and reliable.
- ECO SYSTEM, the new program on the control panel, which optimizes consumptions, making ROUND 45 eco-friendly. Environmental care and good performance at the same time.





CONTROL PANEL WITH DISPLAY



PASSWORD FOR **RELIABILITY AND** EASE OF USE



TOUCH SYSTEM



"BUILT IN" SOLUTION TANK FILTER



DEBRIS TRAY + VACUUM FILTER



ADJUSTABLE AND COMPACT SQUEEGEE



ECO SYSTEM



CHEMICAL MIXING SYSTEM

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
ROUND 45 D 55 TOUCH	10.4222.00	1
ROUND 45 D 55 BC CHEM TOUCH	17.4222.00	1

TECHNICAL DATA

FEVTI	IDES
1	

Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m²/h	2650 - 1590
Power supply		Battery 24V
Installed power	W	1240
Advancement		with traction
IP code	····	IPX3

BATTERIES

туре	Ge	i battery set (2	() pcs) 12v 105AH
Running	time	h - min	2 h and 30 min
Battery c	ompartment dimensions x	No mm×No	340x340x285 X 1
BRUSHE	S		

Cal battan, act (2 pag) 12//10EAb (*)

Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	WxNo	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm ²	25,5 - 16,5 ; 30.5 - 19.7

TRACTION			
Motor rating	W	180	
Driving speed	Km/h	5	
Hill climbing ability (full load)	%	2	

VACUUM

W	550
mbar - mmH ₂ O	1250
l/s	30
dB(A)	64/57 (**)
	mbar - mmH ₂ O

TANK

Туре		Double tank
Cleaning solution tank	I	45
Recovery tank	I	47
Weight (empty/with batteries)	Kg	109 - 189
Dimensions	mm	1210x560x1040

STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush Ø 0.7	40.0003.00
Brush Solution Diffuser	96.0207.00
Detachable brush deck splash guard (without bristles)	24.0265.00
Brush deck splash guard bristles	40.4003.00
Set front+rear natural rubber squeegee blades	96.0091.01
Extra weight for squeegee (1x700 g) (***) (****)	96.0171.00
Gel battery set (2 pcs) 12V 105Ah (*)	18.0001.00
On board charger 24 V 9 A (*)	22.0623.00
Chemical mixing system (*)	96.0048.00

OPTIONAL ACCESSORIES

TYPE	REF. NO.
21" Polypropylene brush Ø 0.9	40.0103.00
21" Polypropylene brush Ø 1.2	40.0303.00
21" Tynex brush Ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.01
Set front + rear polyurethane squeegee blades	96.0055.00
Fleet 4 You (****)	96.0212.00
Fleet & Key 4 You (*****)	96.0213.00

^(*) For BC CHEM version

(**) Silent mode function

(**) 2 on standard equipment

(***) You can use maximum two weights until you reach 1400 g of total additional weight

(*****) On request and to be defined at time of order