

## Walk behind scrubber dryers ROUND 45 - with TRACTION

Round 45 SD 55 TOUCH is the scrubber dryer which has been specifically conceived for daily use. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Cutting edge features and technical equipment make ROUND 45 SD an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. The SD version introduces itself with top-notch innovations.

- **Simply Driven:** a solutions system which is able to combine the best scrubbing and drying performance with an extreme driveability and ease of use: the result is a perfect mix between practicality and cost-effectiveness which guarantees the best operational performance.
- **TOUCH SYSTEM:** the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving ROUND 45 with a finger has never been so practical and intuitive!

ROUND 45 SD 55 TOUCH is available in three versions: one basic and two full-package which include batteries and a battery charger (up to 2 hours and 45 minutes running time for the BC PLUS version).



### PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
ROUND 45 SD 55 TOUCH	10.4232.00	1
ROUND 45 SD 55 BC TOUCH	13.4232.00	1
ROUND 45 SD 55 BC PLUS TOUCH	15.4232.00	1

### TECHNICAL DATA

#### FEATURES

Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m <sup>2</sup> /h	2650 - 1590
Power supply		Battery 24V
Installed power	W	1090
Advancement		with traction
IP code		IPX3

#### BATTERIES

Type	Gel battery set (2 pcs) 12V 76Ah (*) Gel battery set (2 pcs) 12V 105Ah (**)	
Running time	h - min	1 h and 30 min (*) - 2 h and 45 min (**)
Battery compartment dimensions x No	mm x No	340x340x285 X 1

#### BRUSHES

Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	350 x 1
Motor speed	rpm	115
Down pressure - Contact pressure	Kg - g/cm <sup>2</sup>	25,5 - 16,5

#### TRACTION

Motor rating	W	180
Driving speed	Km/h	5
Hill climbing ability (full load)	%	2

#### VACUUM

Motor rating	W	550
Vacuum	mbar - mmHg	1791
Airflow rating	l/s	30
Noise level	dB(A)	63

#### TANK

Type	Double tank	
Cleaning solution tank	l	45
Recovery tank	l	47
Weight (empty/with batteries)	Kg	109 - 189
Dimensions	mm	1210x560x1040

### STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush Ø 0.7	40.0003.00
Brush Solution Diffuser	96.0207.00
Set front+rear natural rubber squeegee blades	96.0091.01
Extra weight for squeegee (1x700 g) (**)(****)	96.0171.00
Gel battery set (2 pcs) 12V 76Ah (*)	18.0000.00
Gel battery set (2 pcs) 12V 105Ah (**)	18.0001.00
On board charger 24V 9A (*) (**)	22.0623.00

### OPTIONAL ACCESSORIES

TYPE	REF. NO.
21" Polypropylene brush Ø 0.9	40.0103.00
21" Polypropylene brush Ø 1.2	40.0303.00
21" Tynex brush Ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.01
Set front + rear polyurethane squeegee blades	96.0055.00
Fleet 4 You (****)	96.0212.00
Fleet & Key 4 You (****)	96.0213.00


(\*) For BC version  
 (\*\*) For BC PLUS version  
 (\*\*\*) 2 on standard equipment  
 (\*\*\*\*) You can use maximum two weights until you reach 1400 g of total additional weight  
 (\*\*\*\*\*) On request and to be defined at time of order



CONTROL PANEL



TOUCH SYSTEM



"BUILT IN" SOLUTION  
TANK FILTER



DEBRIS TRAY +  
VACUUM FILTER



ADJUSTABLE AND  
COMPACT SQUEEGEE