

RUSH 65

RD 55

Ride-on scrubber dryers RUSH SERIES

Rush 65 RD 55 is the ride-on scrubber dryer ideal for medium sized areas. Compact and extremely maneuverable, with 65 liters tank capacity, 55 cm cleaning width and 75 cm squeegee width, Rush can move smoothly even in tight and congested spaces, cleaning quickly and effectively. With its extra down pressure and a squeegee that ensures effective drying on all surfaces, Rush is the ideal solution for thorough and effective cleaning on all types of surfaces. The practical and intuitive control panel, integrated into the steering wheel, allows the user to control and manage all functions of the machine:

- READY TO GO: immediately ready to work! All the machine's main functions can be activated and adjusted simply by pressing a button;
- ECO SYSTEM: the program that reduces consumption and eliminates waste, while maintaining the best cleaning performance and respecting the environment;
- SILENT MODE: the function that reduces the machine's noise level, making it ideal for daily cleaning in sensitive environments such as hospitals, nursing homes and schools.

Thanks to this, and also to the new automatic brush coupling/ uncoupling function, Rush 65 is extremely user-friendly and requires no training, allowing even less experienced operators to use this professional scrubber dryer with ease. Available in three versions, one basic and two full package including batteries and charger, it guarantees a running time of approximately 3½ hours in the BC version and over 3 hours in the BC Lithium version.



The Lithium-Ion batteries have a longer service life and lower maintenance than conventional batteries. They can be recharged at any time, even only partially during short breaks in use, without being damaged.

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RUSH 65 RD 55	10.0665.00	1
RUSH 65 RD 55 BC	13.0665.00	1
RUSH 65 RD 55 BC LITHIUM	14.0665.90	1

TECHNICAL DATA

FEATURES		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theoretical - practical)	m ² /h	3200 - 1920
Power supply		Battery 24V
Installed power	W	1153
Advancement		Traction on rear wheels
IP code		IPX3

BATTERIES

Type	Gel battery set (2 pcs) 12V 105Ah (*) - Lithium battery 24V 100Ah (**)	
Running time	h - min	3 h and 20 min (*) - 3 h and 10 min (**)

Battery compartment dimensions x No mm x No 360x350x325 X 1

BRUSHES

Pad diameter x No	mm - inch x No	530 - 21" x 1
Motor rating x No	W x No	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g/cm ²	20;30,5 - 13;21

TRACTION

Motor rating	W	220
Driving speed	Km/h	6
Hill climbing ability (full load)	%	2
Hill climbing ability (empty)	%	12

VACUUM

Motor rating	W	385
Vacuum	mbar - mmH ₂ O	107 - 1070
Airflow rating	l/s	45
Noise level	dB(A)	63/57 (***)

TANK

Type	Double tank
Cleaning solution tank	l 65
Recovery tank	l 68
Weight (empty/with batteries)	Kg 110 - 181 (*) - 138 (**)
Dimensions	mm 1298x750x1185

STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush Ø 0.8	40.0003.00
Brush Solution Diffuser	96.0207.00
Splashguard	96.0226.00
Set natural rubber squeegee blades (front/rear)	96.0234.00
Gel battery set (2 pcs) 12V 105Ah (*)	22.0724.00
On board battery charger 24V 13A (*)	18.0095.00
Lithium battery 24V 100Ah (**)	18.0112.00
External battery charger 24V 15A (**)	18.0113.00

OPTIONAL ACCESSORIES

TYPE	REF. NO.
21" Polypropylene brush Ø 0,9	40.0103.00
21" Polypropylene brush Ø 1,2	40.0303.00
21" Tynex brush Ø 1,2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.01
Set front + rear polyurethane squeegee blades	96.0234.01
Chemical mixing system	96.0227.00
Headlight kit	96.0180.00
Blinking kit	96.0229.00
Water Stop kit	96.0183.00
Fleet 4 You (****)	96.0212.00
Fleet & Key 4 You (****)	96.0213.00



STEERING WHEEL CONTROL PANEL WITH DISPLAY



"READY TO GO" FUNCTION



ECO SYSTEM



COMPACT DIMENSIONS, COMFORT IN NARROW SPACES



COMPACT SQUEEGEE WITH NATURAL RUBBER BLADES



EXTRA DOWN PRESSURE



SILENT MODE FUNCTION

(*) For BC version
 (**) For BC Lithium version
 (****) Silent mode function
 (****) On request and to be defined at time of order