## **TOOL PRO WDA** 40 L / L AS

## Vacuum cleaners with automatic filter cleaning

Large capacity, sturdy and powerful wet and dry vacuum cleaner approved for L class dust. It is specifically designed to work in environments characterized by the presence of simple dust at moderate risk. Compact and manageable, TOOL PRO WDA 40 Lis ideal for use in environments such as workshops and artisan laboratories. The innovative NONSTOPVAC! system, thanks to the automatic cleaning of the main filter through the reverse air flow, ensures a constant vacuuming and significantly reduces the downtime, allowing the operator to work without interruptions keeping high suction performance. Equipped with the power outlet for electric tool (max power 2400 W) and COMBI Kit for connecting pneumatic accessories (optional) that ensures an operating pressure of up to 10 bar. The machine can be switched on manually or automatically (controlled by the connected tool) and it is also possible to start the vacuum cleaner directly from the flexible hose thanks to the Remote Control Kit (optional). TOOL PRO WDA 40 L is available in two different versions: with antistatic accessories supplied (LAS version), to protect against any electrostatic charges that may occur during work, and with non-antistatic accessories (L version)

REF. NO.

W

W

m<sup>2</sup>

I/s

mbar

mm

m

Κg

mm

13101710001

13201710001 8

1100

2400

0,5

76

250

41

26

20

IPX4

33

625x385x545

PTFE flat filter

NONSTOPVAC!

(M filtration class)

PIECES/PALLET

220-240 V~ 50/60 Hz

**PRODUCT IDENTIFICATION** 

TYPF

TOOL PRO WDA 40 I

**FEATURES** Voltage - Frequency

Main filter

Air flow rate

Vacuum

IP code

Filtration class Accessories Diameter

Dimensions

Power supply cable

Weight (without accessories)

Max power rating

TOOL PRO WDA 40 LAS

**TECHNICAL DATA** 

Rated power (nominal power)

Filtering surface (flat filter)

Filter cleaning system

Container capacity Useful capacity

Useful dust bag capacity

Max power of electrical socket load





COMPACT AND MANAGEABLE



PIVOTING WHEELS WITH BRAKE

## STANDARD ACCESSORIES

| TYPE                                     | REF. NO. |
|--|----------|
| Flexible hose Ø 33 - 4 m (*)             | 6010533  |
| Antistatic flexible hose Ø 33 - 4 m (**) | 6010530  |
| Chromed extension tube 0,5 m (***)       | 2511500  |
| Dry floor tool P340 Ø 36 (*)             | 6010041  |
| Antistatic dry floor tool P340 Ø 36 (**) | 6010042  |
| Connection Ø 33 (*)                      | 2511405  |
| Antistatic connection Ø 33 (**)          | 2511406  |
| Crevice tool Ø 36 (*)                    | 2511520  |
| Antistatic crevice tool Ø 36 (**)        | 2511640  |
| Front intake cap                         | 2001817  |
| PTFE flat filter (M filtration class)    | 2512772  |
| Fleece filter bag (I 20)                 |          |

## OPTIONAL ACCESSORIES

| OPTIONAL ACCESSORIES                         |          |  |
|--|----------|--|
| TYPE   | REF. NO. |  |
| Antistatic flexible hose Ø 29 - 4 m (**)     | 6010531  |  |
| Antistatic flexible hose Ø 29 - 4 m (COMBI)  | 6010548  |  |
| Antistatic flexible hose Ø 29 - 5 m (COMBI)  | 6010543  |  |
| Antistatic flexible hose Ø 29 - 7 m (COMBI)  | 6010544  |  |
| Antistatic flexible hose Ø 29 - 10 m (COMBI) | 6010549  |  |
| Conductive connection Ø 29                   | 2511398  |  |
| Conductive connection coupling Ø 33-29       | 2501244  |  |
| Flexible hose Ø 38 - 4 m                     | 6010536  |  |
| Squeegee tool V340 Ø 36                      | 6010046  |  |
| COMBI Kit                                    | 6689163  |  |
| Remote Control Kit                           | 6689165  |  |
| Tool box adaptors                            | 6689164  |  |
| Transport handle                             | 6340100  |  |
| PE bag                                       | 3001203  |  |
| Fleece filter bag I 20 x 10                  | 3001039  |  |







HOOKS FOR ACCESSORIES AND CABLE HOLDER



POWER TOOL CONNECTION



NONSTOPVAC!



PTFE FLAT FILTER



ANTISTATIC ACCESSORIES (STANDARD FOR LAS VERSION)



COMBIKIT (OPTIONAL)

