

TOOL PRO WDA 40 L / LAS

Vacuum cleaners with automatic filter cleaning



Large capacity, sturdy and powerful wet and dry vacuum cleaner approved for L class dust. It is specifically designed to work in environments characterized by the presence of simple dust at moderate risk. Compact and manageable, TOOL PRO WDA 40 L is ideal for use in environments such as workshops and artisan laboratories. The innovative NONSTOPVAC! system, thanks to the automatic cleaning of the main filter through the reverse air flow, ensures a constant vacuuming and significantly reduces the downtime, allowing the operator to work without interruptions keeping high suction performance. Equipped with the power outlet for electric tool (max power 2400 W) and COMBI Kit for connecting pneumatic accessories (optional) that ensures an operating pressure of up to 10 bar. The machine can be switched on manually or automatically (controlled by the connected tool) and it is also possible to start the vacuum cleaner directly from the flexible hose thanks to the Remote Control Kit (optional).



TOOL PRO WDA 40 L is available in two different versions: with antistatic accessories supplied (LAS version), to protect against any electrostatic charges that may occur during work, and with non-antistatic accessories (L version).

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
TOOL PRO WDA 40 L	13101710001	8
TOOL PRO WDA 40 LAS	13201710001	8

TECHNICAL DATA

FEATURES		
Voltage - Frequency	220-240 V~	50/60 Hz
Max power rating	W	1350
Rated power (nominal power)	W	1100
Max power of electrical socket load	W	2400
Main filter	PTFE flat filter (M filtration class)	
Filtering surface (flat filter)	m ²	0,5
Filter cleaning system	NONSTOPVAC!	
Air flow rate	l/s	76
Vacuum	mbar	250
Container capacity	l	41
Useful capacity	l	26
Useful dust bag capacity	l	20
IP code	IPX4	
Filtration class	L	
Accessories Diameter	mm	33
Power supply cable	m	7
Weight (without accessories)	Kg	21
Dimensions	mm	625x385x545

STANDARD ACCESSORIES

TYPE	REF. NO.
Flexible hose Ø 33 - 4 m (*)	6010533
Antistatic flexible hose Ø 33 - 4 m (**)	6010530
Chromed extension tube 0,5 m (***)	2511500
Dry floor tool P340 Ø 36 (*)	6010041
Antistatic dry floor tool P340 Ø 36 (**)	6010042
Connection Ø 33 (*)	2511405
Antistatic connection Ø 33 (**)	2511406
Crevice tool Ø 36 (*)	2511520
Antistatic crevice tool Ø 36 (**)	2511640
Front intake cap	2001817
PTFE flat filter (M filtration class)	2512772
Fleece filter bag (I 20)	---

OPTIONAL ACCESSORIES

TYPE	REF. NO.
Antistatic flexible hose Ø 29 - 4 m (**)	6010531
Antistatic flexible hose Ø 29 - 4 m (COMBI)	6010548
Antistatic flexible hose Ø 29 - 5 m (COMBI)	6010543
Antistatic flexible hose Ø 29 - 7 m (COMBI)	6010544
Antistatic flexible hose Ø 29 - 10 m (COMBI)	6010549
Conductive connection Ø 29	2511398
Conductive connection coupling Ø 33-29	2501244
Flexible hose Ø 38 - 4 m	6010536
Squeegee tool V340 Ø 36	6010046
COMBI Kit	6689163
Remote Control Kit	6689165
Tool box adaptors	6689164
Transport handle	6340100
PE bag	3001203
Fleece filter bag I 20 x 10	3001039



(*) For L version
(**) For LAS version
(***) 2 on standard equipment



COMPACT AND
MANAGEABLE



PIVOTING WHEELS
WITH BRAKE



HOOKS FOR ACCESSORIES
AND CABLE HOLDER



POWER TOOL CONNECTION



NONSTOPVAC!



PTFE FLAT FILTER



ANTISTATIC
ACCESSORIES
(STANDARD FOR LAS
VERSION)



COMBI KIT (OPTIONAL)